

# DVE™ Viscometer

Precision You Can Trust – Simplicity You Can Afford

## What's Included

- Instrument
- 6 spindles (RV/HA/HB) or 4 spindles (LV)\*  
*\*Threaded Coupling*
- Carrying Case
- Lab Stand (Model G)
- Power Supply  
(Country Cord purchased separately, IEC)

## Optional Accessories

- Small Sample Adapter
- UL Adapter
- Thermosel
- DIN Adapter
- Viscosity Standards
- RV/HA/HB-1 Spindle
- Quick Action Lab Stand
- Temperature Bath
- Quick Connect/Extension Links
- Guard Leg\*  
*\*Not included*



## Features

- **Affordable & Budget-Conscious Design**  
High performance without high costs
- **User-Friendly Interface**  
Simple keypad control and a sharp viewing screen for easy navigation and readability
- **No Complex Calculations Required**  
Provides precise viscosity readings directly in cP, P, mPa•s, or Pa•s
- **Reliable & Repeatable Performance**
  - ±1.0% Accuracy
  - ±0.2% Repeatability
- **Robust & Easy-to-Use Design**  
Compact, bubble level for quick adjustment, and push-button range check for fast setup (FSR)
- **Versatile Compatibility**  
Works seamlessly with a wide range of optional accessories to suit various testing needs
- **18 Speeds for Full Range Capability**  
Covers a broad viscosity range with smooth operation across all models

	VISCOSITY RANGE cP(mPa•s)		SPEEDS (18 Available)	
Model	Min	Max	RPM	Number of Increments
DVELV	1†	2M	.3-100	18
DVERV	100††	13M	.3-100	18
DVEHA	200††	26M	.3-100	18
DVEHB	800††	104M	.3-100	18

M = 1 million cP = Centipoise  
mPa•s = Millipascal•seconds